


## HEAT RESISTANT CABLE TIES

Material: P.A. 6.6  
 Continue temperature: 110° C  
 Short time resistance: -35° C till + 145° C  
 (5000 hours)


## HITZEBESTÄNDIGE KABELBINDER

Material: P.A. 6.6  
 Dauertemperaturbereich: 110° C  
 Kurzzeitig: -35° C bis + 145° C  
 (5000 Stunden)

Typenr.	A mm	B mm	Ø mm	KG	
CV 10025	100	2,5	20	8	100
CV 12025	120	2,5	25	8	100
CV 14025	140	2,5	32	8	100
CV 16025	160	2,5	38	8	100
CV 20025	200	2,5	50	8	100
CV 14036	140	3,6	32	18	100
CV 18836	188	3,6	38	18	100
CV 20036	200	3,6	50	18	100
CV 29236	292	3,6	77	18	100
CV 37036	370	3,6	102	18	100
CV 20048	200	4,8	50	18	100
CV 30048	300	4,8	77	22	100
CV 36848	368	4,8	102	22	100
CV 20076	200	7,6	50	54	100
CV 29276	292	7,6	77	54	100
CV 36876	368	7,6	102	54	100
CV 77590	775	9,0	228	79,4	100



## RELEASABLE CABLE TIES KABELBINDER WIEDERLÖSBAR



Typenr.	A mm	B mm	Ø mm	KG	
GTRN 100 hd	100	7,6	20	22	100
GTRN 120 hd	120	7,6	26	22	100
GTRN 150 hd	150	7,6	35	22	100
GTRN 200 hd	200	7,6	50	22	100
GTRN 250 hd	250	7,6	66	22	100
GTRN 300 hd	300	7,6	80	22	100
GTRN 370 hd	370	7,6	102	22	100

