



Kaapelikengät ja "Abicot"

Cu-putkikaapelikengä

koodi	tyyppi	johdin mm ²	reikä	mitat							paino	pak.
				ØE	ØI	L	ØT	A	L1	C		
010100	T-1,5/4		4			19,0	4,3	8,7	10,0	4,4	0,109	100/2000
010110	T-1,5/5	1,5	5	4,0	2,4	19,0	5,3	8,7	10,0	4,4	0,099	100/2000
010120	T-1,5/6		6			19,0	6,4	9,0	10,0	4,4	0,084	100/2000
010130	T-2,5/4		4			19,0	4,3	8,7	10,0	4,4	0,123	100/2000
010140	T-2,5/5	2,5	5	4,3	2,7	19,0	5,3	8,7	10,0	4,4	0,113	100/2000
010150	T-2,5/6		6			21,0	6,4	10,3	12,0	5,2	0,112	100/1500
010160	T-2,5/8		8			23,0	8,3	11,0	14,0	6,0	0,095	100/1500
010170	T-4/4		4			19,0	4,3	8,7	10,0	4,4	0,158	100/1500
010180	T-4/5	4	5	4,8	3,1	19,0	5,3	8,7	10,0	4,4	0,146	100/1500
010190	T-4/6		6			21,0	6,4	10,3	12,0	5,2	0,145	100/1000
010200	T-4/8		8			26,0	8,3	12,5	17,0	7,0	0,160	100/1000
010210	T-6/4		4			27,0	4,3	10,3	15,0	5,2	0,267	100/1000
010220	T-6/5	6	5	5,5	3,8	27,0	5,3	10,3	15,0	5,2	0,255	100/1000
010230	T-6/6		6			27,0	6,4	10,3	15,0	5,2	0,240	100/1000
010240	T-6/8		8			28,6	8,3	13,9	16,6	7,0	0,216	100/800
010260	T-10/5		5			27,5	5,3	11,9	12,5	5,5	0,427	100/700
010270	T-10/6		6			27,5	6,4	11,9	12,5	5,5	0,407	100/600
010280	T-10/8	10	8	6,9	4,7	30,5	8,3	13,5	15,5	6,8	0,414	100/500
010290	T-10/10		10			30,5	10,3	15,0	15,5	6,8	0,354	100/500
010300	T-10/12		12			37,5	12,8	17,0	22,0	10,0	0,344	100/500
010310	T-16/5		5			27,5	5,3	11,9	12,0	5,5	0,507	100/500
010320	T-16/6		6			27,5	6,4	11,9	12,0	5,5	0,487	100/500
010330	T-16/8	16	8	7,8	5,6	31,0	8,3	13,5	15,5	6,8	0,508	100/500
010340	T-16/10		10			31,5	10,3	16,0	16,0	7,5	0,457	100/400
010350	T-16/12		12			37,5	12,8	17,0	22,0	10,0	0,486	100/300
010360	T-25/6		6			34,0	6,4	13,5	16,0	6,8	0,851	50/600
010370	T-25/8	25	8	9,5	7,1	34,0	8,3	13,5	16,0	6,8	0,804	50/500
010380	T-25/10		10			37,0	10,3	16,0	19,0	8,0	0,902	50/500
010390	T-25/12		12			40,0	12,8	18,0	22,0	10,0	0,794	50/500
010410	T-35/6		6			39,0	6,4	15,7	18,0	8,3	1,353	50/400
010420	T-35/8		8			39,0	8,3	15,7	18,0	8,3	1,298	50/400
010430	T-35/10	35	10	11,0	8,2	43,0	10,3	15,7	22,0	10,0	1,376	50/350
010440	T-35/12		12			43,0	12,8	18,0	22,0	10,0	1,225	50/300
010450	T-35/14		14			48,0	14,5	20,0	27,0	12,0	1,321	50/300
010500	T-50/6		6			45,0	6,4	17,9	18,0	8,3	1,915	20/240
010510	T-50/8		8			45,0	8,3	17,9	18,0	8,3	1,857	20/240
010520	T-50/10	50	10	12,5	9,5	49,0	10,3	17,9	22,0	10,0	1,963	20/200
010530	T-50/12		12			49,0	12,8	17,9	22,0	10,0	1,842	20/200
010540	T-50/14		14			54,0	14,5	22,0	27,0	12,0	1,953	20/200
010550	T-50/16		16			54,0	16,5	26,0	27,0	14,0	1,802	20/200
010570	T-70/8		8			47,6	8,3	21,5	18,0	8,3	2,808	20/160
010580	T-70/10		10			51,6	10,3	21,5	22,0	10,0	2,976	20/160
010590	T-70/12	70	12	15,0	11,5	51,6	12,8	21,5	22,0	10,0	2,835	20/160
010600	T-70/14		14			62,6	14,5	21,5	33,0	16,5	3,434	20/120
010610	T-70/16		16			62,6	16,5	21,5	33,0	16,5	3,276	20/100
010630	T-95/8		8			55,8	8,3	24,7	22,0	10,0	4,084	20/120
010640	T-95/10		10			55,8	10,3	24,7	22,0	10,0	3,769	20/120
010650	T-95/12	95	12	17,0	13,5	55,8	12,8	24,7	22,0	10,0	3,627	20/120
010660	T-95/14		14			66,8	14,5	24,7	33,0	16,5	4,335	20/100
010670	T-95/16		16			66,8	16,5	24,7	33,0	16,5	4,183	20/100
010690	T-120/8		8			72,5	8,3	28,9	33,0	16,5	6,925	10/80
010700	T-120/10		10			72,5	10,3	28,9	33,0	16,5	6,812	10/80
010710	T-120/12	120	12	20,0	15,6	72,5	12,8	28,9	33,0	16,5	6,634	10/80
010720	T-120/14		14			72,5	14,5	28,9	33,0	16,5	6,492	10/80
010730	T-120/16		16			72,5	16,5	28,9	33,0	16,5	6,301	10/80
010750	T-150/10		10			79,0	10,3	30,4	33,0	16,5	8,080	10/70
010760	T-150/12	150	12	21,0	16,5	79,0	12,8	30,4	33,0	16,5	7,898	10/70
010770	T-150/14		14			79,0	14,5	30,4	33,0	16,5	7,752	10/70
010780	T-150/16		16			79,0	16,5	30,4	33,0	16,5	7,557	10/70
010800	T-185/10		10			85,0	10,3	37,0	35,0	16,5	11,406	10/50
010810	T-185/12	185	12	23,6	18,4	85,0	12,8	37,0	35,0	17,0	11,196	10/50
010820	T-185/14		14			85,0	14,5	37,0	35,0	17,0	11,027	10/50
010830	T-185/16		16			85,0	16,5	37,0	35,0	17,0	10,802	10/50
010850	T-240/10		10			91,0	10,3	41,0	35,0	17,0	13,921	5/40
010860	T-240/12	240	12	26,4	21,2	91,0	12,8	41,0	35,0	17,0	13,711	5/40
010870	T-240/14		14			91,0	14,5	41,0	35,0	17,0	13,543	5/40
010880	T-240/16		16			91,0	16,5	41,0	35,0	17,0	13,317	5/40

sofamel
safety & connection



Cu-putkikaapelikenkä

koodi	tyyppi	johdin mm ²	reikä	mitat							paino	pak.	
				ØE	ØI	L	ØT	A	L1	C			
010900	T-300/12	300	12				97,0	12,8	45,6	36,0	17,0	16,118	5/30
010910	T-300/14		14	28,6	23,4		97,0	14,5	45,6	36,0	18,0	15,949	5/30
010920	T-300/16		16				97,0	16,5	45,6	36,0	18,0	15,724	5/30
010940	T-400/12	400	12				104,7	12,8	50,0	47,3	18,0	24,842	5/15
010950	T-400/14		14	32,8	26,8		104,7	16,5	50,0	47,3	24,8	24,426	5/15
010960	T-400/20		20				104,7	21,0	50,0	47,3	24,8	23,263	5/15




=> Saatavana myös isompia putkikaapelikenkiä jopa 1000mm² asti

Cu-putkikaapelikenkä 45° kulmassa

koodi	tyyppi	johdin mm ²	reikä	mitat							paino / 100	pak.
				ØE	ØI	L	ØT	A	L1	C		
007270	T45-10/6	10	6	6,9	4,7	10	6,4	11,9	12,5	5,5	0,400	100/400
007280	T45-10/8		8				8,3	13,5	15,5	6,8	0,520	100/500
007320	T45-16/6	16	6	7,8	5,6	11	6,4	11,9	12,0	5,5	0,490	100/400
007330	T45-16/8		8				8,3	13,5	15,5	6,8	0,510	100/300
007370	T45-25/8	25	8	9,5	7,1	13	8,3	13,5	16,0	6,8	0,800	50/300
007380	T45-25/10		10				10,5	16,0	19,0	8,0	0,820	50/300
007420	T45-35/8	35	8	11,0	8,2	16	8,3	15,7	18,0	8,3	1,280	50/300
007430	T45-35/10		10				10,5		22,0	10,0	1,360	50/300
007520	T45-50/10	50	10	12,5	9,5	19	10,5	17,9	22,0	10,0	1,950	20/200
007530	T45-50/12		12				13,0				1,850	20/200
007580	T45-70/10	70	10	15,0	11,5	21	10,5	21,5	22,0	10,0	2,850	20/120
007590	T45-70/12		12				13,0				2,700	20/120
007660	T45-95/14	95	14	17,0	13,5	24	14,5	24,7	33,0	16,5	4,200	20/100
007670	T45-95/16		16				16,5				4,000	20/100
007720	T45-120/14	120	14	20,0	15,6	28	14,5	28,9	33,0	16,5	6,900	10/60
007730	T45-120/16		16				16,5				6,700	10/60
007770	T45-150/14	150	14	21,0	16,5	32	14,5	30,4	33,0	16,5	8,000	10/50
007780	T45-150/16		16				16,5				7,800	10/50
007830	T45-185/16	185	16	23,6	18,4	34	16,5	37,0	35,0	17,0	11,800	10/40
007880	T45-240/16	240	16	26,4	21,2	38	16,5	41,0	35,0	17,0	13,800	5/30

Cu-putkikaapelikenkä 90° kulmassa

008270	T90-10/6	10	6	6,9	4,7	10	6,4	11,9	12,5	5,5	0,400	100/400
008280	T90-10/8		8				8,3	13,5	15,5	6,8	0,520	100/500
008320	T90-16/6	16	6	7,8	5,6	11	6,4	11,9	12,0	5,5	0,490	100/400
008330	T90-16/8		8				8,3	13,5	15,5	6,8	0,510	100/300
008370	T90-25/8	25	8	9,5	7,1	13	8,3	13,5	16,0	6,8	0,800	50/300
008380	T90-25/10		10				10,5	16,0	19,0	8,0	0,820	50/300
008420	T90-35/8	35	8	11,0	8,2	16	8,3	15,7	18,0	8,3	1,280	50/300
008430	T90-35/10		10				10,5		22,0	10,0	1,360	50/300
008520	T90-50/10	50	10	12,5	9,5	19	10,5	17,9	22,0	10,0	1,950	20/200
008530	T90-50/12		12				13,0				1,850	20/200
008580	T90-70/10	70	10	15,0	11,5	21	10,5	21,5	22,0	10,0	2,850	20/120
008590	T90-70/12		12				13,0				2,700	20/120
008660	T90-95/14	95	14	17,0	13,5	24	14,5	24,7	33,0	16,5	4,200	20/100
008670	T90-95/16		16				16,5				4,000	20/100
008720	T90-120/14	120	14	20,0	15,6	28	14,5	28,9	33,0	16,5	6,900	10/60
008730	T90-120/16		16				16,5				6,700	10/60
008770	T90-150/14	150	14	21,0	16,5	32	14,5	30,4	33,0	16,5	8,000	10/50
008780	T90-150/16		16				16,5				7,800	10/50
008830	T90-185/16	185	16	23,6	18,4	34	16,5	37,0	35,0	17,0	11,800	10/40
008880	T90-240/16	240	16	26,4	21,2	38	16,5	41,0	35,0	17,0	13,800	5/30



Cu-Eristämätön haarukkakenkä

koodi	tyyppi	johdin mm ²	reikä	mitat								paino / 100	pak.	
				ØE	ØI	A	T	C	L1	L	G			
030100	CU-1,5/3		3			5,8	3,2	6,3			15,8		0,058	100/-
030110	CU-1,5/4	1,5	4	3,4	1,7	6,4	4,3	6,3	4,8	15,4	0,8		0,056	100/-
030120	CU-1,5/5		5			9,5	5,3	7,0			15,8		0,082	100/-
030130	CU-2,5/3		3			6,0	3,2	5,0			14,5		0,065	100/-
030140	CU-2,5/4	2,5	4	4,1	2,3	6,4	4,3	6,3	4,8	15,4	0,8		0,065	100/-
030150	CU-2,5/5		5			9,5	5,3	7,3			16,8		0,081	100/-
030160	CU-2,5/6		6			12,0	6,4	11,0			22,0		0,125	100/-
030170	CU-6,4		4			9,5	4,3	7,5			19,5		0,137	100/-
030180	CU-6,5	6,0	5	5,6	3,4	9,5	5,3	7,5	6,8	19,5	1,0		0,144	100/-
030190	CU-6/6		6			13,5	6,4	12,2			25,5		0,166	100/-
030200	CU-6/8		8			13,5	8,5	12,2			25,5		0,180	100/-

Cu-Eristämätön jatkoholkki






koodi	tyyppi	johdin mm ²	mitat			paino	pak.
			ØE	ØI	L		
015100	M-1,5	1,5	4,0	2,4	22,2	0,119	100/2000
015110	M-2,5	2,5	4,3	2,7	22,2	0,127	100/1500
015120	M-4	4	5,0	3,3	25,0	0,215	100/1000
015130	M-6	6	5,5	3,8	25,0	0,255	100/1000
015140	M-10	10	6,9	4,4	25,0	0,400	100/600
015150	M-16	16	8,0	5,6	29,0	0,560	100/400
015160	M-25	25	9,5	7,1	29,0	0,730	50/500
015170	M-35	35	11,0	8,2	35,0	1,210	50/300
015180	M-40	40	11,0	9,1	35,0	0,970	50/300
015190	M-50	50	12,5	9,5	35,0	1,510	20/260
015200	M-70	70	15,0	11,5	45,0	2,710	20/140
015210	M-95	95	17,0	13,5	47,0	3,410	20/100
015220	M-120	120	20,0	15,6	52,0	5,400	10/90
015230	M-150	150	21,0	16,5	59,1	6,600	10/70
015240	M-185	185	25,4	20,2	65,0	9,600	10/50
015250	M-240	240	28,5	22,1	75,0	12,500	5/40
015260	M-300	300	31,7	24,3	90,0	16,200	5/15
015270	M-400	400	34,8	26,8	90,0	30,100	5/5

Al-putkikaapelikenkä

koodi	tyyppi	johdin mm ²	mitat						paino	pak.
			ØE	ØI	ØT	L	A	C		
115100	TBE-25	25	11,0	6,5	8,5	52,0	16,0	9,2	0,880	25/250
115110	TBE-35	35	13,3	7,8	8,5	56,0	19,0	8,2	1,300	25/175
115120	TBE-50	50	15,2	9,8	13,0	64,0	22,0	12,5	1,700	25/100
115130	TBE-70	70	17,0	11,0	13,0	73,0	25,0	11,5	2,500	10/80
115140	TBE-95	95	19,3	12,6	13,0	81,0	28,0	13,5	3,400	10/60
115150	TBE-120	120	22,0	14,0	13,0	94,0	32,0	14,7	5,400	10/50
115160	TBE-150	150	25,0	15,5	13,0	102,0	35,0	14,7	8,660	10/30
115170	TBE-185	185	28,1	18,3	13,0	112,0	40,0	16,7	11,000	5/20
115180	TBE-240	240	32,0	19,5	15,0	125,0	45,0	18,7	16,400	5/15
115190	TBE-300	300	34,0	23,0	17,5	140,0	46,5	22,2	18,000	3/-


Bi-metalli kaapelikenkä Cu-Al ns. vaihtokenkä

koodi	tyyppi	johdin mm ²	mitat						paino	pak.
			ØE	ØI	L1	L	ØT	ØP		
110110	TBF-25	25	20,0	6,5	46,0	84,0	12,8	25,0	7,200	-/30
110120	TBF-35	35	20,0	8,0	46,0	84,0	12,8	25,0	7,200	-/30
110130	TBF-50	50	20,0	9,0	46,0	84,0	12,8	25,0	7,000	-/30
110140	TBF-70	70	20,0	11,0	46,0	84,0	12,8	25,0	7,000	-/30
110150	TBF-95	95	20,0	12,5	46,0	84,0	12,8	25,0	6,300	-/30
110160	TBF-120	120	25,0	13,7	62,5	107,0	12,8	30,0	13,500	-/30
110170	TBF-150	150	25,0	15,5	62,5	107,0	12,8	30,0	12,200	-/30
110180	TBF-185	185	32,0	17,0	64,0	117,0	14,5	36,0	20,100	-/15
110190	TBF-240	240	32,0	19,5	64,0	117,0	14,5	36,0	22,600	-/15
110200	TBF-300	300	36,0	23,3	90,0	157,0	16,3	42,0	33,400	-/10
110210	TBF-400	400	36,0	26,0	90,0	157,0	16,3	42,0	30,200	-/10



Cu-Eristämätön piikkikenkä

koodi	tyyppi	johdin mm ²	mitat					paino	pak.
			ØE	ØI	L	A	L1		
025100	CP-1,5	1,5	3,4	1,7	17,0	1,9	10,0	0,050	100/2500
025110	CP-2,5	2,5	4,1	2,4	17,0	1,9	10,0	0,059	100/2000
025120	CP-6	6	5,7	3,7	20,0	2,7	10,0	0,152	100/1500
025130	CP-10	10	6,0	5,0	23,5	4,6	11,5	0,248	100/1000
025140	CP-16	16	7,5	6,0	28,0	6	14,5	0,425	100/600
025150	CP-25	25	9,0	7,0	31,0	7	15,5	0,537	100/400
025160	CP-35	35	11,0	9,0	38,0	9	18,0	0,890	100/200
025170	CP-50	50	12,0	10,5	42,0	10	20,0	1,330	50/150





Kytkäliitin 10-nap. Ns. halkaistu pultti

koodi	tyyppi	johdin mm ²	mitat			paino	pak.
			A	H	L		
231100	ADRI-6	6	28,5	19,5	164,0	5,340	-/10
231110	ADRI-10	10	28,5	24,0	204,0	11,600	-/10
231120	ADRI-16	16	28,5	27,2	214,0	14,540	-/10
231130	ADRI-25	25	28,5	29,3	224,0	16,660	-/10
231140	ADRI-35	35	28,5	34,2	261,0	28,660	-/10

Cu-Levykaapelikenkä

koodi	tyyppi	johdin mm ²	reikä	mitat							paino	pak.
				ØI	ØT	L	A	C	G			
020100	TD-1,5/3		3		3,2		6,0	11,0			0,055	100/2000
020110	TD-1,5/4	1,5	4	1,6	4,3	5,0	8,0	12,0	5,0		0,070	100/2000
020120	TD-1,5/5		5		5,3		10,0	13,0			0,084	100/2000
020130	TD-2,5/3		3		3,2		6,0	11,0			0,064	100/1000
020140	TD-2,5/4		4		4,3		8,0	12,0			0,077	100/1000
020150	TD-2,5/5	2,5	5	2,3	5,3	5,0	10,0	14,0	5,0		0,080	100/1000
020160	TD-2,5/6		6		6,5		11,0	16,0			0,110	100/1000
020170	TD-2,5/8		8		8,4		14,0	17,0			0,135	50/1000
020180	TD-6/4		4		4,3		8,0	14,0			0,139	100/700
020190	TD-6/5		5		5,3		10,0	15,0			0,157	100/700
020200	TD-6/6	6	6	3,6	6,5	6,0	11,0	16,0	6,0		0,168	100/700
020210	TD-6/8		8		8,4		14,0	19,0			0,213	100/700
020220	TD-6/10		10		10,5		18,0	21,0			0,279	100/700
020230	TD-10/5		5		5,3		10,0	16,0			0,229	100/600
020240	TD-10/6		6		6,5		11,0	17,0			0,240	100/600
020250	TD-10/8	10	8	4,5	8,4	8,0	14,0	20,0	8,0		0,290	100/600
020260	TD-10/10		10		10,5		18,0	21,0			0,349	100/600
020270	TD-10/12		12		13,0		22,0	23,0			0,414	100/600
020280	TD-16/5		5		5,3		11,0	20,0			0,406	100/300
020290	TD-16/6		6		6,5		11,0	20,0			0,381	100/300
020300	TD-16/8	16	8	5,8	8,4	10,0	14,0	22,0	10,0		0,425	100/300
020310	TD-16/10		10		10,5		18,0	24,0			0,502	100/300
020320	TD-16/12		12		13,0		22,0	26,0			0,600	100/300
020330	TD-25/6		6		6,5		12,0	25,0			1,400	50/200
020340	TD-25/8		8		8,4		16,0	25,0			1,480	50/200
020350	TD-25/10	25	10	7,5	10,5	11,0	18,0	26,0	11,0		1,560	50/200
020360	TD-25/12		12		13,0		22,0	31,0			1,920	50/200
020370	TD-25/16		16		17,0		28,0	35,0			2,320	50/150
020380	TD-35/6		6		6,5		15,0	26,0			1,920	50/150
020390	TD-35/8		8		8,4		26,0	26,0			1,920	50/100
020400	TD-35/10	35	10	9,0	10,5	12,0	18,0	27,0	12,0		2,040	50/100
020410	TD-35/12		12		13,0		22,0	31,0			2,360	50/100
020420	TD-35/16		16		17,0		28,0	36,0			2,880	50/100
020430	TD-50/6		6		6,5		18,0	34,0			1,760	25/100
020440	TD-50/8		8		8,4		18,0	34,0			1,720	25/100
020450	TD-50/10	50	10	11,0	10,5	16,0	18,0	34,0	16,0		1,680	25/100
020460	TD-50/12		12		13,0		22,0	36,0			1,840	25/100
020470	TD-50/16		16		17,0		28,0	40,0			2,120	25/100



sofamel
safety & connection

020480	TD-70/6		6		6,5		22,0	38,0		2,600	10/50
020490	TD-70/8		8		8,4		22,0	38,0		2,600	10/50
020500	TD-70/10	70	10	13,0	10,5	18,0	22,0	38,0	2,0	2,600	10/50
020510	TD-70/12		12		13,0		22,0	38,0		2,500	10/50
020520	TD-70/16		16		17,0		28,0	42,0		2,800	10/50
020530	TD-95/8		8		8,4		24,0	42,0		4,100	10/40
020540	TD-95/10		10		10,5		24,0	42,0		4,100	10/40
020550	TD-95/12	95	12	15,0	13,0	20,0	24,0	42,0	2,5	4,000	10/40
020560	TD-95/16		16		17,0		28,0	44,0		4,100	10/40
020570	TD-120/8		8		8,4		24,0	44,0		5,600	10/30
020580	TD-120/10		10		10,5		24,0	44,0		6,200	10/30
020590	TD-120/12	120	12	16,5	13,0	22,0	24,0	44,0	3,0	5,400	10/30
020600	TD-120/16		16		17,0		28,0	48,0		5,700	10/30
020610	TD-150/10		10		10,5		30,0	50,0		8,400	5/30
020620	TD-150/12	150	12	19,0	13,0	24,0	30,0	50,0	3,2	8,600	5/30
020630	TD-150/16		16		17,0		30,0	50,0		7,700	5/30
020640	TD-185/10		10		10,5		36,0	50,0		11,100	5/30
020650	TD-185/12	185	12	21,0	13,0	28,0	36,0	50,0	3,5	10,800	5/30
020660	TD-185/16		16		17,0		36,0	50,0		10,700	5/30
020670	TD-240/10		10		10,5		38,0	56,0		15,200	5/15
020680	TD-240/12	240	12	23,5	13,0	32,0	38,0	56,0	4,0	15,000	5/15
020690	TD-240/16		16		17,0		38,0	56,0		14,700	5/15

Eristetty pyöröpistoke

koodi	tyyppi	johdin mm ²	väri	mitat					paino	pak.
				ØA	L	L2	ØI	L1		
305150	ACM-1,5	1,5	●	3,96	20,2	8,7	3,5	9,5	0,928	100/1000
305160	ACM-2,5	2,5	●				4,3		1,028	100/1000

Eristetty pyöröliitin

koodi	tyyppi	johdin mm ²	väri	mitat					paino	pak.
				ØI2	L	L2	ØI1	L1		
305170	ACH-1,5	1,5	●	3,96	24	8,5	2,7	10,0	1,250	100/500
305180	ACH-2,5	2,5	●		25		3,2	11,0	1,362	100/500

